

November 28, 2011

Edcon Power Tongs + Oilfield Services Ltd.
Box 209
Lac La Biche, Alberta
T0A 2C0

Equipment Certification

Rig No.:	N/A
Equipment:	AOT Side Door Casing Elevator
Model:	9 5/8" - 90° - 65 Ton
Customer P.O.:	N/A
Serial No.:	EQ# 950
Inspection Report No.:	H-27189
Alco Sales/Engineering No.:	18392-E
APEGGA Permit to Practice No.:	P10702
Alco Shop Work Order # :	15369


The above-mentioned elevator required a Level IV inspection (as per Canadian Association of Oilwell Drilling Contractors, R.P. 2.0), applicable repairs, and certification for service.

A magnetic particle (MT) inspection was conducted on October 27, 2011, after the elevator was completely disassembled and sandblasted.

Repair procedures were developed based on the MT inspection report as well as a thorough visual examination performed by qualified personnel with Alco Inc.

Based on the final inspection on November 28, 2011, after load testing, it is our opinion that the elevator is a safe operating unit and may be returned to service within the manufacturer's original rating and specification.

This certification is valid for a period of 500 operating days, as per the recommendations provided by the Canadian Association of Oilwell Drilling Contractors, or until the elevator has been damaged either as a result of operation, transportation or handling.



Report # : NDT17716-TS1071		Asset ID : 12402 (Tool# 950)	
Client :	Edcon Power Tongs & Oilfield - Lac La Biche		Branch : Lac La Biche
Inspection Date :	Oct 23, 2017		Client WO :
Inspection Location :	Lac La Biche		Client PO : Jay
Client Ref :	MPI Inspection		

Red Flame Industries Testing Equipment

Yoke				
Make	Model	Serial#	Calibration	Expires Date
Magnaflux	Y-1	762	Feb 16, 2017	Feb 16, 2018

Magnetic Particle Examination Information and Results

Material Type: Carbon Steel

Temperature: 0° to 20°C

Surface Preparation: Painted

Acceptance Criteria: Red Flame Engineering Acceptance

Technique Used: AC Dry Powder - Continuous

Procedure: MT-1 Rev. 8.3

In accordance with codes: ASME V Article 7, ASME B30.20

Results**Magnetic Particle Examination Conducted On - Casing Elevator - 9.625" - 244.475MM
65 Ton - 12402 (Tool# 950)**

Visible Dry Particle Examination Conducted With AC Powered Yoke.

Multidirectional Field Achieved By Repositioning Yoke At Right Angles In Each Area Examined.
Powder Applied With Hand Blower. Batch Number 16F104 Powder Removal By Light Exhalation.
Minimum White Light At Examination Surface: 1000 Lux. Particle Size 2-6 μ m. Particle Color: YELLOW.

Examination Conducted On 9" Elevator; All Accessible Surfaces, Transition Areas And Lift Points On Fully Assembled Painted Elevator As Requested.

Results: No Relevant Indications Were Detected At The Time Of Examination.

See Photo.

Red Flame Industries Personnel Information

Technician: Tom Schulz

SNT-MT2

SNT-UT2

SNT-PT2

CGSB-MT2 - 17965

Assistant:

Signature:





950.jpg

Report Attachments